



## Bodendüsen

### Fugendüsen



R+M Nr.	↔	∅
265 020	370 mm	58 mm



R+M Nr.	↔	∅
265 022	370 mm	58 mm



R+M Nr.	↔	∅
264 019 3	350 mm	45 mm



R+M Nr.	↔	∅
264 019 4	350 mm	45 mm

### Schrägrohrdüse



R+M Nr.	↔	∅
263 616	170 mm	35 mm

### Rohrbürste



R+M Nr.	∅	∅
263 629	100 mm	35 mm
263 628	200 mm	35 mm

### Gummisaugrohr



R+M Nr.	∅
264 028	45 mm

### Flexible Fugendüsen



Drehbar. Diebstahlsicherung durch 3-teiliges Clip-Verriegelungssystem

R+M Nr.	↔	∅
264 019 12	375 mm	DN 38



Drehbar. Einfache Montage durch Schraubgewinde

R+M Nr.	↔	∅
264 019 1	420 mm	DN 38



Mit Innensteg 18 cm. Drehbar. Einfache Montage durch Schraubgewinde

R+M Nr.	↔	∅
264 019 11	420 mm	DN 38



Drehbar. Einfache Montage durch Schraubgewinde

R+M Nr.	↔	∅
265 019 1	420 mm	DN 50



Mit Innensteg 18 cm. Drehbar. Einfache Montage durch Schraubgewinde

R+M Nr.	↔	∅
265 019 11	420 mm	DN 50

